

#### Features

- Measures AC/DC voltage and current, resistance, capacitance, frequency, diode and continuity
- Built-in non-contact voltage detector and double molded plastic housing
- 4,000-count backlit LCD display
- Low battery indicator and auto shut-off
- CAT III 600V safety rating
- Includes test leads and batteries

#### Specifications

##### AC/DC Voltage

Range:	AC: 4, 40, 400, 600V DC: 400mV, 4, 40, 400, 600V
Accuracy:	AC: 4, 40V $\pm(1.2\% \text{ rdg.} + 5 \text{ dgt.})$ 400, 600V $\pm(2\% \text{ rdg.} + 10 \text{ dgt.})$ DC: 400mV $\pm(1\% \text{ rdg.} + 8 \text{ dgt.})$ 4, 40V $\pm(0.5\% \text{ rdg.} + 5 \text{ dgt.})$ 400, 600V $\pm(0.8\% \text{ rdg.} + 5 \text{ dgt.})$
Resolution:	AC: 0.01, 0.01, 0.1, 1V DC: 0.1mV, 0.001, 0.01, 0.1, 1V

##### AC/DC Current

Range:	400 $\mu$ A, 4, 40, 400mA
Accuracy:	AC: 400 $\mu$ A, 4, 40, 400mA $\pm(2\% \text{ rdg.} + 8 \text{ dgt.})$ DC: 400 $\mu$ A, 4, 40, 400mA $\pm(1.8\% \text{ rdg.} + 5 \text{ dgt.})$
Resolution:	0.1 $\mu$ A, 0.001, 0.01, 0.1mA

##### Resistance

Range:	400 $\Omega$ , 4, 40, 400k $\Omega$ , 4, 40M $\Omega$
Accuracy:	400 $\Omega$ , 4, 40, 400k $\Omega$ : $\pm(1\% \text{ rdg.} + 5 \text{ dgt.})$ 4M $\Omega$ : $\pm(1.2\% \text{ rdg.} + 10 \text{ dgt.})$ 40M $\Omega$ : $\pm(2\% \text{ rdg.} + 10 \text{ dgt.})$
Resolution:	0.1, 1, 10, 100 $\Omega$ , 1, 10k $\Omega$

##### Capacitance

Range:	50, 500nF, 5, 50, 100 $\mu$ F
Accuracy:	50nF: $\pm(4\% \text{ rdg.} + 30 \text{ dgt.})$ 500nF: $\pm(3\% \text{ rdg.} + 15 \text{ dgt.})$ 5, 50, 100 $\mu$ F: $\pm(4\% \text{ rdg.} + 10 \text{ dgt.})$
Resolution:	0.01, 0.1, 1, 10, 100nF

##### Frequency

Range:	9.999Hz to 60kHz
Accuracy:	$\pm(0.1\% \text{ rdg.} + 5 \text{ dgt.})$
Resolution:	0.001Hz to 0.001Mz



Continued...

#### General Specifications

Range Selection:	Autorangeing
Display:	4,000 count LCD display
Display Hold:	Yes
Diode Test:	Yes
Continuity Check:	Audible signal if resistance $\leq 10\Omega$
Non-Contact Voltage Detector:	Yes
Auto Power Off:	Yes (after 30 minutes)
Power Supply:	2 x AAA
Low Battery Indicator:	Yes
Fuse Protection:	Yes
Replaceable Test Leads:	No
Overrange Indicator:	Yes (OL)
Overvoltage Category:	CAT III 600V
Product Certifications:	CE
Operating Temperature:	32 to 104°F (0 to 40°C)
Storage Temperature:	14 to 122°F (-10 to 50°C)
Dimensions:	4.4 x 2.3 x 1.4" (112 x 58 x 35mm)
Weight:	6.3oz (180g)

#### R5099-KIT

Compact Multimeter with NCV Kit

Includes:  
R5099 Compact Multimeter,  
R5210 Receptacle Tester with GFCI,  
R5100 Non-Contact AC Voltage  
Detector, and carrying case



Model	Description
R5099	Compact Multimeter with NCV
R5099-KIT	Compact Multimeter with NCV Kit
R5099-NIST	Compact Multimeter with NCV with NIST